AD-A130 025 AN APPROXIMATION OF THE EXPECTED STOWED KILLS IN SEQUENTIAL 1 X M ENGAGEM..(U) ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND ABERDEEN PROVI.. L D JOHNSON 1/1

UNCLASSIFIED JUN 83 ARBRL-TR-02494 SBI-AD-F300 266 F/G 12/1 NL



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS

(12)

AD

TECHNICAL REPORT ARBRL-TR-02494

(Supersedes IMR No. 683)

AN APPROXIMATION OF THE EXPECTED STOWED KILLS IN SEQUENTIAL 1 X M ENGAGEMENTS

Lawrence D. Johnson

June 1983

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

DTIC FILE COPY

Destroy this report when it is no longer needed.
Do not return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U. S. Department of Commerce, Springfield, Virginia 22161.

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS BEFORE COMPLETING FORM

1. REPORT NUMBER: TECHNICAL REPORT ARBRL-TR-02494
2. GOVT ACCESSION NO.:
3. RECIPIENT'S CATALOG NUMBER:

4. TITLE (and Subtitle): AN APPROXIMATION OF THE EXPECTED STOWED KILLS IN SEQUENTIAL 1 X M ENGAGEMENTS
5. TYPE OF REPORT & PERIOD COVERED:
6. PERFORMING ORG. REPORT NUMBER:

7. AUTHOR(s): L. D. Johnson
8. CONTRACT OR GRANT NUMBER(s):

9. PERFORMING ORGANIZATION NAME AND ADDRESS:
US Army Ballistic Research Laboratory
ATTN: DRDAR-BLB
Aberdeen Proving Ground, MD 21005

10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS: 1L162618AH80

11. CONTROLLING OFFICE NAME AND ADDRESS:
US Army Armament Research & Development Command
US Army Ballistic Research Laboratory (DRDAR-BLA-S)
Aberdeen Proving Ground, MD 21005

12. REPORT DATE: June 1983
13. NUMBER OF PAGES: 12

14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office):

15. SECURITY CLASS. (of this report): UNCLASSIFIED
15a. DECLASSIFICATION/DOWNGRADING SCHEDULE:

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

Supersedes BRL IMR 655.

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Stowed Kills
Expected Values

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

An equation is developed which approximates the expected number of red tanks killed per blue tank stowed load in sequential 1 X M tank engagements.

TABLE OF CONTENTS

		Page
	INTRODUCTION	5
I.	BACKGROUND	5
II.	THE DERIVATION AND EQUATION	5
III.	EXAMPLES	9
	1 Blue Versus 1 Red	9
	1 Blue Versus 3 Red	9
IV.	SUMMARY	10
	DISTRIBUTION LIST	11

A

INTRODUCTION

Contained herein is a derivation of an equation which has been used to convert 1 X M duel simulation outputs into a measure of performance which integrates lethality, vulnerability and ammunition depletion rate.

Section I discusses the impetus for the derivation; Section II derives the equation; Section III discusses example applications, and Section IV summarizes the results.

I. BACKGROUND

The Ballistic Research Laboratory (BRL), working with the Army Materiel Systems Analysis Activity (AMSAA), has developed a computer model which simulates "N X M" tank engagements. Among the various outputs of this model are the probability that each of all possible terminal states can occur and the average ammunition depletion of each element associated with each state.

During a dry-run exercise of the program, it was observed that several systems had similar probable final engagement outcomes, but dissimilar burdens (in terms of ammunition depletion). It became evident that some method was required to integrate the burden directly* into the performance measure. It was decided that a measure which indicated the probable number of tanks killed per unresupplied system in a sequence of 1 X M engagements would be of interest.

This report discusses the derivation of such a measure.

II. THE DERIVATION AND EQUATION

The problem that faced us was that the expected number of tanks killed by blue in a sequence of 1 X M engagements had to be approximated with only the following information at hand:

P_{ij} ≐ probability that exactly (i-1) blue tanks and (j-1) red tanks are killed at the termination** of a 1 X M engagement

N_{ij} ≐ the average number of rounds expended per blue tank given the final state indicated by P_{ij}

L ≐ original ammunition load.

Before leaping into the derivation, let's define a few terms which will help keep the equations relatively compact.

---

* *The model does implicitly address the burden by limiting each element's ammunition load.*

** *The game ends when one side is completely destroyed or when no element can fire, e.g., all are destroyed or out of ammunition.*

Term	Example	Definition
m	$= M + 1$	The maximum dimensions of the matrix (P_{ij}) associated with a 1 X M engagement.
P_S	$= \sum_{j=1}^{m} P_{1j}$	Probability of blue survival in a 1 X M engagement. Note: It is assumed that $P_S < 1.0$.
E_n	$= \sum_{i=1}^{2} \sum_{j=1}^{m} N_{ij} * P_{ij}$	Expected number of blue rounds expended per engagement
$E_{n/S}$	$= \sum_{j=1}^{m} N_{1j} * P_{1j}/P_S$	Expected number of blue rounds expended in a survived engagement
$E_{n/\bar{S}}$	$= \sum_{j=1}^{m} N_{2j} * P_{2j}/(1-P_S)$	Expected number of blue rounds expended in an engagement not survived
E_K	$= \sum_{i=1}^{2} \sum_{j=1}^{m} (j-1) * P_{ij}$	Expected number of red tanks destroyed in an engagement
$E_{K/S}$	$= \sum_{j=1}^{m} (j-1) * P_{1j}/P_S$	Expected number of red tanks destroyed in an engagement survived by blue
$E_{K/\bar{S}}$	$= \sum_{j=1}^{m} (j-1) * P_{2j}/(1-P_S)$	Expected number of red tanks destroyed in a blue attrited engagement
E_R	$= E_{K/S}/E_{n/S}$	An indicator of the number of red tanks killed per blue round fired in an engagement survived* by blue
N	$=$ integer $\left\{\frac{L}{E_{n/S}}\right\}$	The average number of successful engagements implied by an ammunition load consisting of L rounds
N_R	$= L - N * E_{n/S}$	The average number of rounds remaining after N engagements have been survived*
$E_{K/R}$	$= N_R * E_R$	An approximate number of red tanks killed by N_R rounds.

*Is capable of engaging future targets.

With the preceding information at hand, we approximate the expected value equation by using engagement averages for the possible values of the number of red tanks killed, and by limiting the possible number of successful engagements to the average number of successful engagements implied by the original ammunition complement, i.e.,

$$E_T = \left\{ \sum_{i=0}^{N-1} (i * E_{K/S} + E_{K/\bar{S}}) P_S^i (1 - P_S) \right\} + (N * E_{K/S} + E_{K/R}) * P_S^N \qquad (1)$$

where E_T is approximate expected kills per ammunition load. Note that the term $(i * E_{K/S} + E_{K/\bar{S}})$ is the average number of red tanks killed given that blue was attrited during the (i+1) engagement. Also note that $P_S^i(1 - P_S)$ is the probability that blue was attrited on specifically the (i+1) engagement.

The term on the far right refers to the situation where blue survives all N engagements. Notice that the term $E_{K/R}$ is a type of "fudge factor" to indicate the potential kills of the residual rounds stowed after N successful engagements.

The series contained in Equation (1) can be solved in closed form by remembering that

$$\sum_{i=0}^{N-1} a^i = \frac{1 - a^N}{1 - a}$$

$$\sum_{i=0}^{N-1} i a^i = a \frac{\partial}{\partial a} \left\{ \sum_{i=0}^{N-1} a^i \right\} .$$

With these relations, Equation (1) can first be reduced to

$$E_T = E_{K/\bar{S}} (1 - P_S^N) + E_{K/S} \frac{P_S}{(1 - P_S)} (1 - P_S^N) + E_{K/R} P_S^N \qquad (2)$$

which can further be contracted to

$$E_T = \frac{(1 - P_S^N)}{(1 - P_S)} \left\{ E_{K/\bar{S}} (1 - P_S) + E_{K/S} P_S \right\} + E_{K/R} P_S^N \qquad (3)$$

which then is seen to be

$$E_T = \frac{(1 - P_S^N)}{(1 - P_S)} E_K + P_S^N E_{K/R} . \qquad (4)$$

At this point we can only hope that the equation cannot be reduced further or it might completely disappear!

One item which must be verified is that Equation (4) is continuous with respect to N_R, i.e., does the example "fudge factor" work at the extremes of $N_R = 0$ and $N_R = E_{n/S}$. When $N_R = 0$ there are no residual rounds and since $E_{K/R} = 0$ under this condition, the factor is correct for this extreme. However, as $N_R \to E_{n/S}$ the E_T equation should approach the next order value. This can be shown by observing that

$$\lim_{N_R \to E_{n/S}} \frac{(1 - P_S^N)}{1 - P_S} E_K + P_S^N E_{K/R} = \frac{(1 - P_S^N)}{1 - P_S} E_K + \lim_{N_R \to E_{n/S}} (P_S^N E_{K/R})$$

$$= \frac{(1 - P_S^N)}{1 - P_S} E_K + P_S^N * (E_{n/S} * E_{K/S} / E_{n/S})$$

$$= \left(\frac{1 - P_S^{N+1}}{1 - P_S}\right) E_K .$$

Since the factor is consistent at the extremes, it appears reasonable. The implicit assumption concerning $E_{K/R}$ which will remain challengeable is that $E_{K/R}$ is linear with respect to N_R.

Another item of interest concerns the degenerate cases; namely, $N = 1$ and $N_R = 0$ and $N \to \infty$. Since $N = 1$ and $N_R = 0$ imply that there is, on average, insufficient ammunition to entertain subsequent engagements, the answer of $E_T = E_K$ of Equation (4) is intuitively palatable.

Finally, taking $N \to \infty$ implies an unlimited load and the result of

$$E_T = \frac{E_K}{(1 - P_S)}$$

is again consistent since it represents the exchange ratio for the engagement, i.e., the ratio of the expected number of red tanks killed to the expected number of blue tanks killed.

Bolstered by the absence of inconsistencies, the next section will discuss a few examples.

III. EXAMPLES

1 Blue Versus 1 Red

Assume that L = 50, and that

$$P_{ij} = \begin{bmatrix} .1 & .5 \\ .2 & .2 \end{bmatrix} ; \quad N_{ij} = \begin{bmatrix} 50 & 4 \\ 2 & 1 \end{bmatrix}$$

then $E_K = (.5 + .2) * 1 = .7$

$P_S = .1 + .5 = .6$

$E_{n/S} = (50 * .1 + 4 * .5)/.6 = 11.67$

$N = \text{integer } (50/11.67) = \text{integer } (4.29) = 4$

$N_R = 50 - 4 * 11.67 = 3.32$

$E_{K/R} = 3.32 * (.83/11.67) = .24$

$\lim_{N \to \infty} E_T = .7/(1 - .6) = 1.75$

$$E_T = \frac{(1 - .6^4)}{(1 - .6)} .7 + .6^4(.24) = 1.55 .$$

Thus, for this example the exchange ratio = 1.75
expected kills per engagement = .7
expected kills per ammunition load = 1.55

1 Blue Versus 3 Red

Assume that L = 50, and

$$P_{ij} = \begin{bmatrix} .0 & .2 & .15 & .05 \\ .05 & .25 & .2 & .1 \end{bmatrix}$$

$$N_{ij} = \begin{bmatrix} 0 & 3 & 4 & 5 \\ 3 & 4 & 5 & 6 \end{bmatrix}$$

then $E_K = (.2 + .25) * 1 + (.15 + .2) * 2 + (.05 + .1) * 3 = 1.6$

$P_S = .0 + .2 + .15 + .05 = .4$

$E_{n/S} = (0 * .0 + 3 * .2 + 4 * .15 + 5 * .05)/.4 = 3.625$

$N = \text{integer } (50/3.625) = \text{integer } (13.793) = 13$

$$N_R = 50 - (13 * 3.625) = 2.875$$

$$E_{K/R} = 2.875 * (1.625/3.625) = 1.29$$

$$\lim_{N \to \infty} E_T = 1.6/(1 - .4) = 2.67$$

$$E_T = \frac{1 - .4^{13}}{(1 - .4)} 1.6 + .4^{13} (1.29) = 2.67$$

i.e., exchange rate = 2.67
expected kills per engagement = 1.6
expected kills per load = 2.67

IV. SUMMARY

An heuristic equation has been developed which allows the transformation of 1 X M tank engagement output data into a measure of performance which integrates the effects of lethality, vulnerability and ammunition depletion. The equation:

$$E_T = \frac{(1 - P_S^N)}{1 - P_S} E_K + P_S^N E_{K/R}$$

is an approximation of the expected number of red tanks killed per blue tank (given a finite ammunition load). An assumption, implicit to the equation, is that E_K remain constant as long as the residual ammunition load is greater than (or equal to) the average ammunition expended in a successful engagement. Although the assumption will tend to provide higher than the true answer at small values of N, the equation appears to be reasonable in terms of providing a good "feel" of the interplaying benefits and burdens of system performance.

It is a rather trival exercise to generalize the terms of the equation such that the approximation would be relevant to N X M engagements. However, the cumulation of assumptions* supporting such an exercise makes the author uncomfortable and by nature of the generalization, the resultant equation may attain more credence than it warrants. Thus, temporarily at least, the development terminates at this point.

*For example, the current TANKWARS output does not differentiate between rounds of ammo fired by attrited blue tanks versus surviving blue tanks. Thus the average number of rounds expended [illegible]

DISTRIBUTION LIST

No. of Copies	Organization
12	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22314
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMD-ST 5001 Eisenhower Avenue Alexandria, VA 22333
1	Commander US Army Armament Research and Development Command ATTN: DRDAR-TDC Dover, NJ 07801
1	Commander US Army Armament Research and Development Command ATTN: DRDAR-LCS-D, Mr. Rubin Dover, NJ 07801
2	Commander US Army Armament Research and Development Command ATTN: DRDAR-TSS Dover, NJ 07801
1	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L Rock Island, IL 61299
1	Director US Army ARRADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB-TL Watervliet, NY 12189
1	Commander US Army Aviation Research and Development Command ATTN: DRDAV-E 4300 Goodfellow Boulevard St. Louis, MO 63120
1	Director US Army Air Mobility Resear and Development Laboratory Ames Research Center Moffett Field, CA 94035
1	Commander US Army Communications Rese and Development Command ATTN: DRSEL-ATDD Fort Monmouth, NJ 07703
1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703
1	Commander US Army Missile Command ATTN: DRDMI-R Redstone Arsenal, AL 35898
1	Commander US Army Missile Command ATTN: DRDMI-YDL Redstone Arsenal, AL 35898
1	Commander US Army Tank Automotive Command ATTN: DRSTA-TSL Warren, MI 48090

DISTRIBUTION LIST

No. of Copies	Organization
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL White Sands Missle Range NM 88002
1	Commander US Army Armor Center & School ATTN: ATZK-CD-MS COL DeMont Fort Knox, KY 40121
2	President US Army Armor & Engineer Board ATTN: ATZK-AE-CV COL Fleming MAJ D. Knox Fort Knox, KY 40121
2	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905
1	Commander 9th Infantry Division ATTN: AFVO-TB-MS, CPT Martin Fort Lewis, WA 98433
1	Commander US Naval Surface Weapon Ctr ATTN: G31 Dahlgren, VA 22448
1	Commander Marine Corps Development and Education Command ATTN: Plans & Studies Div Quantico, VA 22134

No. of Copies	Organization
	ABERDEEN PROVING GROUND
	Dir, USAMSAA ATTN: DRXSY-D DRXSY-MP, Mr. H. Cohen Mr. W. Brooks Mr. B. Siegel
	Cdr, USATECOM ATTN: DRSTE-TO-F
	Dir, USACSL, Bldg E3516, EA ATTN: DRDAR-CLB-PA DRDAR-CLN DRDAR-CLJ-I

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below, tear out this sheet, fold as indicated, staple or tape closed, and place in the mail. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____

2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

_____

_____

_____

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

_____

_____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

_____

_____

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

_____

_____

_____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

_____

_____

FOLD HERE

Director
US Army Ballistic Research Laboratory
ATTN: DRDAR-BLA-S
Aberdeen Proving Ground, MD 21005

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON, DC
POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Director
US Army Ballistic Research Laboratory
ATTN: DRDAR-BLA-S
Aberdeen Proving Ground, MD 21005

FOLD HERE

END

FILMED

7-83

DTIC